

## PA IPM07A

Color screen Desktop IP Microphone



### Features

- ▶ Supports hands-free and non-hands-free dual-mode calls: External gooseneck microphone, built-in speaker, supports hands-free calling; with microphone interface, can connect a professional microphone for non-hands-free calling.
- ▶ Equipped with a 7-inch full-color LCD display, supports touch operation, can directly configure IP addresses, and view terminal status.
- ▶ Supports network search configuration, can directly address the configuration.
- ▶ Supports paging and conference calls.
- ▶ Supports two-way intercom function: Two-way intercom between terminals is possible.
- ▶ Has multiple one-touch call touch buttons, convenient for calling different zones.
- ▶ Has one-touch help and intercom functions, enabling quick connections.
- ▶ Supports online network upgrades.
- ▶ Has a monitoring function for listening to environmental sounds captured by other terminals.
- ▶ Supports both static IP and DHCP, suitable for cross-segment and cross-router configurations, making setup convenient.
- ▶ Equipped with a standard 3.5mm audio interface, can connect a dedicated microphone for easy expansion of non-hands-free calling, suitable for private communication.
- ▶ Supports one local line output, which can be connected to an external power amplifier.
- ▶ Has a broadcasting function, suitable for general exams or radio broadcasting needs.
- ▶ Supports U-disk playback, can play files from a U-disk on other terminals.
- ▶ Has a U-KEY interface, supports user operation authorization. (Optional)

### PA IPM07A

#### Main Specifications

Technical parameters	Power supply	DC12V/2A
	Network interface	1 set of RJ45
	Transmission rate	10/100Mbps
	Support protocol	ARP, UDP, TCP/IP, ICMP, IGMP(multicast)
	Sampling rate	8kHz to 48kHz
	Line In input level	400mV (standard 3.5mm audio interface)
	Line Out output level	0.775V (Standard 3.5mm audio interface)
	Frequency response	40Hz to 20KHz(±3dB)
	Total Harmonic distortion (THD@1W)	1% or less
	Signal-to-noise ratio	> 80dB
	Operating temperature	0°C to 50°C

#### Appearance

Parameters	Dimensions	240*150*56mm
	Display	7 "resistive touch screen
	Net weight	1.45 KG
	Standby power consumption	< 5W

## Notes

- ▶ Do not install near any heat source, such as radiators, heat storage, stoves and other heating equipment
  - ▶ Never place this product in water leakage or splashing environment
  - ▶ Do not place any source of danger on this product (such as containers with liquid or lit candles, etc.)
  - ▶ Prevent the power cord from being trampled and squeezed; Especially in plug, power socket, equipment power cord outlet position
  - ▶ In lightning weather or long-term use, please unplug the power plug of the product
  - ▶ All maintenance should be carried out by qualified maintenance personnel
-



Picture of the whole machine

