

PA LSP20A-Wm

IP Network speaker



Features

- ▶ Built-in 2×20W power output, along with high-quality speakers.
- ▶ The sub-box is a 20W/8Ω fixed impedance speaker with built-in high-quality speakers, producing loud and clear sound.
- ▶ The product features a unique hook design and wall-mounted installation method, making construction simple, safe, and reliable.
- ▶ Supports remote online upgrade of terminal programs, facilitating project maintenance and management.
- ▶ Supports cross-segment and cross-router communication, serving as an internet terminal in the WAN, and supports DHCP.
- ▶ Adapts to the network environment, activating buffering and packet retransmission in poor network conditions.
- ▶ Features red-green dual-color LED status indicators for easy troubleshooting.

PA LSP20A-Wm

Main specifications

Technical parameters	Network interface	Standard RJ45
	Power supply	AC 220V/50Hz
	Power output	2 * 20 w / 8 Ω
	Audio bit rate	32Kbps to 320Kbps Adaptive
	Frequency response	40Hz to 20KHz
	Signal-to-noise ratio	≥85dB
	Audio format	MP3
	Total harmonic distortion	≤0.1% (@1W)
	Transmission rate	10/100Mbps
	Support protocol	ARP, UDP, TCP/IP, ICMP, IGMP
	Operating environment	-10°C ~ +60°C
	Storage environment	-20°C to +70°C

Function

Function description	High-end wooden box, exquisite appearance, beautiful sound quality, cost-effective
	The power amplifier is integrated with the sound box, making the connection simpler and the use more convenient
	The main and auxiliary boxes can be used separately and independently, or can be used together to provide full frequency stereo output
	The main box is the system device of this product, using embedded real-time operating system, built-in 2×20W power output (one power for itself, one power for the auxiliary box) and high-quality speakers
	The sub-box is 20W /8Ω constant resistance speaker, built-in high-quality speaker, loud and clear sound
	Chic hook design, unique wall-mounted installation mode, simple construction, safe and reliable

Points to note

- ▶ Do not install near any heat source, such as radiators, heat storage, stoves and other heating equipment
- ▶ Never place this product in water leakage or splashing environment
- ▶ Do not place any source of danger on this product (such as containers with liquid or lit candles, etc.)
- ▶ Please use the accessories/accessories specified by the manufacturer
- ▶ Prevent the power cord from being trampled and squeezed; Especially in plug, power socket, equipment power cord outlet position
- ▶ In lightning weather or long-term use, please unplug the power plug of the product
- ▶ Please clean the dust on the product and the power plug and socket regularly
- ▶ All repairs should be carried out by qualified maintenance personnel. This product should be repaired in case of any damage, such as power cord or plug damage, liquid spilled on the product, the product gets rained or damp, does not work properly, or falls



Picture of the whole machine

LP-G1005A



LP-G1005B

