

PA LSP20A-AP

POE active sound column



Features

- ▶ 2 audio inputs and 1 audio output;
- ▶ 1-channel volume adjustment
- ▶ Power supply mode: POE power supply
- ▶ Equipped with installation brackets, easy to install;
- ▶ Power: 20W;


Technical specifications
PA LSP20A-AP
Main specifications

Technical parameters	Power supply	POE 48V 0.65A/DC 15V 2A
	Power	20W
	Input sensitivity	350mV
	Frequency response	(-10dB) 120Hz -15KHz
	Signal to noise ratio	87dB ± 3dB
	Sound pressure level	(average) 105dB ± 3dB
	Color	White (RAL 9003)
	Material	Shell: Aluminum Front grille: aluminum Upper and lower covers: ABS
	Interface specifications	RJ45 * 1, RCA male * 1, Phoenix interface (audio input interface * 1, audio output interface * 1), DC IN * 1
	Product dimensions	(L * W * H) 152mm x 103mm x 392mm
	Working temperature	-15 ° C to+55 ° C
	Storage temperature	-10 ° C to+50 ° C
	Relative humidity	<95%

Points to note

- ▶ Do not install near any heat source, such as radiators, heat storage, stoves and other heating equipment
- ▶ Never place this product in water leakage or splashing environment
- ▶ Do not place any source of danger on this product (such as containers with liquid or lit candles, etc.)
- ▶ Please use the accessories/accessories specified by the manufacturer
- ▶ Prevent the power cord from being trampled and squeezed; Especially in plug, power socket, equipment power cord outlet position
- ▶ In lightning weather or long-term use, please unplug the power plug of the product
- ▶ Please clean the dust on the product and the power plug and socket regularly
- ▶ All repairs should be carried out by qualified maintenance personnel. This product should be repaired in case of any damage, such as power cord or plug damage, liquid spilled on the product, the product gets rained or damp, does not work properly, or falls



Picture of the whole machine

