

PA LSP06A-Wm

Wall-mounted speaker



Features

- ▶ Extraordinary voice and music reproduction effects
- ▶ Simple and convenient power setting
- ▶ Easy and quick installation, with flexible assembly options.
- ▶ Conforming to CE standard


Technical specifications
PA LSP06A-Wm
Main specifications

Technical parameters	Input Power	3W/6W (100V)
	Rated Impedance	2K Ω (5W)/1K Ω (10W)
	Sound Pressure Level	91dB (1M/1W)
	Frequency Response	150Hz to 15kHz
	Speaker Unit Size	6.5" * 1
	Dimensions	312*210*85mm
	Material	ABS
	Weight	1.7 kg
	Mounting Method	Wall-mounted
	Operating Temperature	-25°C to +55°C
	Storage Temperature	-40°C to +70°C
	Relative Humidity	<95%

Notes

- ▶ Do not place the device in an area that is too cold or too hot
 - ▶ Ensure that the working environment of the equipment is well ventilated, so as not to cause damage to the equipment due to heat and high temperature during working
 - ▶ In rainy and humid days or long time without use, please unplug the power plug
 - ▶ Before removing or reinstalling any part of the equipment and external equipment, be sure to unplug the power plug to ensure that the equipment is completely disconnected from the power grid
 - ▶ When the equipment is faulty, non-professionals without permission, please do not privately open the casing for maintenance, so as to avoid accidents or aggravate the damage of the equipment
 - ▶ Do not place any corrosive chemicals near or on the equipment
-



Picture of the machine

